

Creative PC-900B Handheld Capnograph & Oximeter

Multi Flow Rate
Sidestream
Technology



Flexible

- Monitors EtCO₂ / FICO₂, RR, SpO₂ & PR. Switchable readout in kPa / mmHG / %
- Sidestream technology for intubated and NON Intubated patients
- Adjustable pump rates allow for use of both standard luer sampling lines (use T4F Water Trap for luer sampling lines / T4M for Microflow lines)
- Wide range of sampling lines and O₂/ CO₂ masks available

Simple




- Clear full colour display provides both graphical trends and plethysmographic wave forms plus digital numeric values
- Compact and lightweight, ideal for emergency and rescue situations. Comes with free rubber bumper and table stand
- Simple user adjustable apnoea and visual alarms for all main parameters
- Graphic trend display and storage for up to 24 hours memory

Affordable

- Long life lithium rechargeable batteries, AC mains 5V USB charger supplied and vehicle charger options available
- Simple, annual calibration requirement with calibration kit available for customers or in house PROACT calibration
- FREE data download PC software, for data analysis and review (use with supplied charger cable)
- Optional Heavy Duty Paramedic Carry Case

Creative PC-900B Handheld Capnograph & Oximeter

Parameter Specifications

ETCO₂ and FICO₂		Operating Conditions	
Mode of measurement:	Sidestream (non-dispersive infrared)	Temperature	-5 to 50°C
Range:	0 to 150mmHg or 0 to 20kPa or 0 to 20% (v/v)	Humidity	<93% (non-condensing) = <29.45 hPa
Accuracy	±2mmHg for EtCO ₂ range 0-40mmHg ±5% for EtCO ₂ range from 41 to 70mmHg ±8% for EtCO ₂ range from 71 to 100mmHg Over 100mmHg ±10%	Atmospheric pressure	70 to 120kPa
Update Frequency	Option of every breath or 10, 20 or 30 seconds	Storage Conditions	
Warm up time	< 20 seconds	Temperature	-30 to 70°C
Sample flow rate	50 to 250ml/min User adjustable. Default=100ml/min	Humidity	<93% (non-condensing)
Memory	24 hours on screen trend and numeric	Atmospheric pressure	50 to 120kPa
Respiration Rate		Dimensions	
Range	3 - 150 breaths/minute	Size	72 x 155 x 40mm (W x H x D)
Accuracy	±1% of reading or ±1 breath/min whichever is greater	Weight	600g (Weight of sampling kit on ETT/LMA: <25g)
Memory	24 hours	Warranty and Calibration	
SpO₂		One year warranty on main unit	
Range	0 to 100%	Self-zeroing calibration, annual calibration check recommended	
Accuracy	±2% for SpO ₂ range from 70 to 100% ±3% for SpO ₂ range from 50 to 69%	IP rating	IP32 when used with specified supplied with blue silicone case
Memory	24 hours	CE & Compliance	
Pulse Rate		93/42/EEC Medical Directive Compliant	
Range	30 to 250bpm	CE 0123	Shenzhen Creative Industry Co. Ltd
Accuracy	±2% for PR range from 30 - 250bpm	Icon Menu	
Memory	24 hours		ON / OFF
Power			Menu
AC Input	100V to 250V, 50Hz / 60 Hz with 5V mini USB adapter. Optional Vehicle 12V to 5V Mini USB Charger Lead		Alarm / Silence
Battery			Cursor Select Adjust
Type	Built-in rechargeable lithium battery pack (3.6V, 3000mAh)		Enter
Charging Time	4 hours		
Operating time	10 hours		



Shown with optional PROBAG-CAP

Accessories - Contact us for a full list of accessories, sensors and calibration kits

CR-PC900B-11	PC-900B Hand Held EtCO ₂ & SpO ₂ (Creative) Monitor with Case Includes Adult SpO ₂ Soft Sensor, CO ₂ Sampling Kit, USB Cable and Charger	
CR664522	Water Trap/Filter T4F for Creative PC-900B Monitor (Female Luer Connection)	Pack of 10
CR664523	Water Trap/Adapter T4M for Creative PC-900B Monitor (Male Microflow)	Pack of 10
WL99370010	Elbow Connector - 22F / 15M with Port	Box of 50
PBSL08003	PRO-Breathe Gas Sampling Line, Luer Lock Male/ Male 1.27mm ID x 3.0m	Box of 50
CR5550-010	Pole Mount Clamp for Creative PC-900B Monitor	Single
PROBAG-CAP	Heavy Duty Cushioned Carry Case	Single
CR-12VDC9B	12V DC Vehicle Power Adapter to 5V DC Mini USB - 3m Length	Single

